

SECTION 1 IDENTIFICATION

PRODUCT NAME CC-14	PRODUCT TYPE: Aerosol – Chain & Cable Lubricant DOT CLASS ORM-D CONSUMER COMMODITY
Manufactured For: DYNACCO, INC. PO BOX 27 17461 – 147 TH ST. S.E. MONROE, WA 98272	Information Phone:: 360-794-8974 24-Hour Emergency Phone: CHEM-TEL (800) 255-3924 Date Prepared: October 15, 2001 Reviewed: March 14, 2008

SECTION 2 IDENTITY INFORMATION AND HAZARDOUS INGREDIENTS

Chemical Name:	CAS No.:	TLV:
Heavy Naphthenic Petroleum Oil	64742-52-5	5 mg/m ³ as mist
Paraffin Oil	64742-62-7	5 mg/m ³ as mist
Propane	74-98-6	2500ppm
Butane	106-97-8	800ppm
Molybdenum Disulfide	1317-33-5	10 mg/m ³ as dust

SECTION 3 PHYSICAL DATA

Boiling Point: <0 to 212 ^o F	Solubility in Water: Nil
Vapor Density(Air=1): Heavier than air	Specific Gravity(H ₂ O=1): 0.80 ⁺ 0.05
Evaporation Rate: Slower than Ether	pH: NA

SECTION 4 FIRE AND EXPLOSION HAZARD DATA

Flash Point: >200 ^o F	Flash Point(Propellant): < 0 ^o F
Flammable Limits(Propellant): LEL: 1.9 UEL: 9.5	
Extinguishing Media: Use water fog, dry chemical or carbon dioxide.	
Special Fire Fighting Procedures: Aerosol cans may rupture when heated.	
Unusual Fire and Explosion Hazards: Heated cans may burst.	

SECTION 5 REACTIVITY DATA

Stability: Unstable_____	Stable __X__
Incompatibility (Materials to Avoid): None known.	Conditions to Avoid: High temperatures.
Hazardous Decomposition or Byproducts: In fire, will decompose to carbon dioxide, carbon monoxide	
Hazardous Polymerization: Will not occur	

SECTION 6 STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storing: When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

STORE AT TEMPERATURES BELOW 120 ^o F	KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME.
KEEP AWAY FROM CHILDREN	FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY
FOR USE BY TRAINED PERSONNEL ONLY	KEEP CONTAINER CLOSED DURING STORAGE

SECTION 7 HEALTH HAZARDS AND FIRST AID

Effects of Overexposure:

SKIN: Skin irritant. Will cause defatting of skin. Effects are reversible.

EYES: Eye irritant. Will cause redness and burning sensation.

INHALATION: Effects of overexposure include irritation of respiratory tract, headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.

INGESTION: Aspiration hazard if swallowed.

First Aid Procedures:

SKIN: Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get medical attention. Remove contaminated clothing and launder before reuse. EYES: Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Seek medical attention.

INHALATION: Remove person to fresh air. If irritation persists, give oxygen, get medical attention.

INGESTION: DO NOT induce vomiting. Seek medical attention immediately.

Note: Never give anything by mouth to an unconscious or convulsing victim. Keep person warm and quiet

SECTION 8 SPECIAL PROTECTION INFORMATION

Respiratory Protection: Self-contained breathing apparatus if above TLV limit.

Ventilation: Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit.

Protective Gloves: None required if spraying.

Eye Protection: As with all cleaners, Dynacco supports employee safety as priority #1. Therefore, we recommend the use of safety glasses or chemical splash goggles. Other Protective Equipment: Long sleeves and long pants.

Work/Hygienic Practices: Do not smoke while using. Wash hands after use.

SECTION 9 SPILL OR LEAK PROCEDURE

Steps To Be Taken In Case Material Is Released or Spilled: Use absorbent sweeping compound to soak up material.

Put into container. Dispose as hazardous waste.

Waste Disposal Method: Dispose as hazardous waste in accordance with EPA RCRA.

SECTION 10 REGULATORY INFORMATION

SARA Title III, Section 313 Components:

None

This information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition. We make no warranties, express or implied, and assume no liability in connection with any use of this information. CC-14 Chain & Cable Lubricant