

HMIS CODES: (Based on Aerosol Conc.) H - 0 F - 1 R - 0 P - A
NFPA RATING: H - 0 F - 2 R - 0 Spec-

IDENTITY AND MANUFACTURER'S INFORMATION

PRODUCT NAME GLIDE	PRODUCT TYPE: Aerosol - Coating for Glass & Plexiglas DOT CLASS ORM-D CONSUMER COMMODITY
MANUFACTURED FOR: DYNACCO, INC. PO BOX 27 17461 - 147 TH ST. S.E. MONROE, WA 98272	INFORMATION PHONE: 360-794-8974 24-HOUR EMERGENCY: CHEM-TEL (800) 255-3924 DATE PREPARED: NOVEMBER 1, 2007

SECTION II - INGREDIENTS

CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TLV-TWA
Isopropyl Alcohol	67-63-0	1 - 10	NO	NO	NO	400 ppm	200 ppm
Liquefied Petroleum Gas	68476-86-8	1 - 10	NO	NO	NO	1000 ppm	1000 ppm

SECTION III - PHYSICAL DATA

Aerosol Concentrate:

Boiling Point:	212°F	Specific Gravity (H ₂ O=1)@70°F:	0.99
pH:	9.8	Solubility In Water:	Complete
Appearance/Odor:	Clear, colorless liquid with light alcohol odor	Vapor Density(Air=1):	>1

Total Contents:

Total VOC %:	9.53%	Vapor Pressure (can; psig @72°F):	50
--------------	-------	-----------------------------------	----

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point (Conc.):	None to Boiling (212° F - T.O.C)	Flammability (as per CSMA Flame Projection Test):	Non-Flammable Spray
Extinguishing Media:	Foam, CO ₂ , Dry Media		
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.		
Unusual Fire and Explosion Hazards:	Exposure to temperature above 120° F may cause bursting.		

SECTION V - REACTIVITY DATA

Stability:	Material Stable.	Hazardous Polymerization:	Will not Occur.
Incompatibility:	Avoid contact with strong oxidizing agents.		
Hazardous Decomposition Products:	Carbon Dioxide, Carbon Monoxides.		

SECTION VI - STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.
Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 1 Aerosol.
Store in a cool, dry area away from heat or open flame.

SECTION VII - HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause irritation accompanied by stinging, tearing, redness, and swelling of eyes.
Skin: May cause mild irritation. Frequent or prolonged contact may cause redness, burning, and drying and cracking of skin. May aggravate existing skin conditions.
Inhalation: Inhalation of small amounts of vapor or mist is not likely to cause harmful effects. Inhalation of large amounts may irritate the upper respiratory tract and have a slight anesthetic effect. Prolonged overexposure can cause central nervous system depression, mild, temporary changes in the liver, effects on heart and breathing rates, low blood pressure, loss of coordination, confusion, lung edema, and kidney damage.
Ingestion: Ingestion of small amounts during normal handling and use is not likely to cause harmful effects. Ingestion of large amounts can cause severe gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause lung inflammation and other lung injury.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
Skin: Wash with soap and water. If irritation persists seek medical attention.
Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII - SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.
Ventilation: Provide local exhaust to keep air concentrations of ingredients listed in Section II below acceptable limits.
Protective Gloves: Use chemical resistant gloves if hand contact will be made.
Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION IX - SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.