

SECTION I - PRODUCT IDENTIFICATION	
PRODUCT NAME SS-40	PRODUCT TYPE: Aerosol - Non-Flammable Solvent DOT CLASS: ORM-D Consumer Commodity
MANUFACTURED FOR: DYNACCO, INC. PO BOX 27 17461 - 147 TH ST. S.E. MONROE, WA 98272	INFORMATION PHONE: 360-794-8974
	24-HOUR EMERGENCY: CHEM-TEL 800-255-3924
	DATE PREPARED: 11-06-07

SECTION II - INGREDIENTS							
CHEMICAL NAME	CAS #	%WT	313/Chem	Skin	Carcinogen	PEL	TLV - TWA
Trichloroethylene	79-01-6	90-100	YES	NO	YES	100 ppm	10 ppm
Isopropyl Alcohol	67-63-0	01-10	NO	NO	NO	400 ppm	400 ppm
Butylene Oxide	106-88-7	< 0.5	YES	NO	YES	N/E	2 ppm*
Carbon Dioxide Propellant	124-38-9	01-10	NO	NO	NO	10,000 ppm	10,000 ppm

*Recommended Workplace Environmental Exposure Level (WEEL).

SECTION III - PHYSICAL DATA Data Below Based On Aerosol Concentrate Only: pH: N/A Solubility In Water: negligible Appearance/Odor: Clear, colorless liquid / Ether-like odor Vapor Pressure of can (psig @70°F): 90	Boiling Point: ~186° F Vapor Density(Air=1): 4. 5 Specific Gravity (H ₂ O=1)@75°F: 1.419 Data Below Based On Total Contents: Total VOC %: 97 %
---	---

SECTION IV - FIRE AND EXPLOSION DATA Flash Point (of Concentrate Only): None to Boiling Extinguishing Media: Foam, CO ₂ , Dry Media Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing. Unusual Fire and Explosion Hazards: Exposure to temperature above 120° F may cause bursting.	Flammability (as per USA Flame Projection Test): Non-Flammable Spray
--	--

SECTION V - REACTIVITY DATA Stability: Material Stable. Incompatibility: Avoid contact with strong oxidizing agents, Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide, Hydrogen Chloride, Small amount of Phosgene.	Hazardous Polymerization: Will not occur.
--	---

SECTION VI - STORAGE AND HANDLING KEEP OUT OF REACH OF CHILDREN. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120° F.	For Industrial and Institutional use only. NFPA Code 30B Rating: Level 1 Aerosol.
---	--

SECTION VII - HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:
 Eyes: Causes severe irritation, redness, tearing, and blurred vision.
 Skin: Frequent or prolonged contact may cause irritation and possibly dermatitis. May aggravate existing skin conditions.
 Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract and central nervous system effects, including dizziness nausea, headaches, unconsciousness, or death. Long-term overexposure may cause liver or kidney injury..
 Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis and pulmonary edema.

FIRST AID PROCEDURES:
 Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.
 Skin: Wash with soap and water. If irritation persists seek medical attention.
 Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
 Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII - SPECIAL PROTECTION DATA

Respiratory Protection: If workplace exposure limits are exceeded (see Section II), use a NIOSH approved air purifying respirator for single short-term exposure. Use a positive-pressure, air-supplied respirator for multiple or long-term exposures.
Ventilation: Provide local exhaust to keep air concentrations of ingredients listed in Section II below established exposure limits.
Protective Gloves: Use chemical resistant gloves to help prevent skin contact.
Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION IX - SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.
WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.