

# MSDS

## MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA's Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

HMIS CODES: H - 1 F - 1 R - 0 P - B  
NFPA RATING: H - 1 F - 1 R - 0 Spec-

IDENTITY AND MANUFACTURER'S INFORMATION					
PRODUCT NAME <b>ULTRA HIGH-TEMP GREASE</b>			PRODUCT TYPE: Grease to 2100°F DOT CLASS: Oils, Lubricating, NOI Non-Hazardous		
MANUFACTURED FOR: <b>DYNACCO, INC.</b> PO BOX 27 17461 - 147 <sup>TH</sup> ST. S.E. MONROE, WA 98272		INFORMATION PHONE: 360-794-8974 24-HOUR EMERGENCY: CHEM-TEL (800) 255-3924 MSDS Number RL735 Revision E DATE PREPARED: April 20, 1993			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
<b>COMPONENTS-CHEMICAL NAMES AND COMMON NAMES</b> (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
<b>PETROLEUM OIL MIXTURE</b>	8002-05-9	No	5mg/M3 TWA for oil mist	5mg/M3 TWA for oil mist	d
<b>WARNING: This product contains a chemical or chemicals known to the State of California to cause cancer.</b>					
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A		Specific Gravity (H <sub>2</sub> O=1): 0.8			
Vapor Pressure: PSIG @ 70°F (Aerosols): N/A		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): <0.01			
Vapor Density (Air = 1): 12		Evaporation Rate (= 1): N/A			
Solubility in Water: Negligible		Water Reactive: No			
Appearance and Odor: Metallic silver gel, with oil odor.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) N/A		Auto Ignition Temperature N/A		Flammability Limits in Air by % in Volume: % LEL: N/D % UEL: N/D	
FLASH POINT AND METHOD USED (non-aerosols): >400°F COC SPECIAL			EXTINGUISHER MEDIA: Dry chemical (preferred), carbon dioxide, foam, water.		
FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Empty containers may retain product residue including flammable or explosive vapors. Do not cut, drill, grind or weld on or near full, part full or empty drum.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [ X ] STABLE [ ] UNSTABLE		HAZARDOUS POLYMERIZATION [ ] WILL [ X ] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Chlorine or oxygen.		Conditions to Avoid: Oxidizing atmospheres.			
Hazardous Decomposition Products: Thermal: unidentified organics. Oxidation: oxides of carbon.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [ ] INHALATION [ ] INGESTION [ X ] SKIN ABSORPTION [ ] EYE [ ] NOT HAZARDOUS					
ACUTE EFFECTS:					
Inhalation: Not expected to be a problem. Massive exposure to vapors or fumes may cause headaches, dizziness, and/or drowsiness.					
Eye Contact: May cause irritation.			Skin Contact: May cause irritation.		
Ingestion: May cause vomiting, nausea, diarrhea.					
CHRONIC EFFECTS: None noted.					
Medical Conditions Generally Aggravated by Exposure: Dermatitis.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Wash with large amounts of water. If irritation persists, call a physician.					
Skin Contact: Remove contaminated clothing. Wash with soap and water.					
Inhalation: Remove to fresh air.					
Ingestion: DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): None required.					
Protective Gloves: Oil resistant types.			Eye Protection: Splash goggles or safety glasses.		
Ventilation Requirements: None required in excess to normal ventilation.					
Other Protective Clothing & Equipment: Oil resistant apron.					
Hygienic Work Practices: Do not work in oil soaked clothing. Wash after handling.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Stop flow, dike spill, eliminate all ignition sources, absorb on inert material and scrape up.					
Waste Disposal Methods: Dispose of in accordance with local, state and federal regulations.					
Precautions To Be Taken In Handling & Storage: Avoid prolonged exposure to mist and vapors. Avoid flames, sparks and hot surfaces. Keep containers closed. Shelf life one year.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Empty containers may contain explosive gas.					

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF February 6, 2008. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.

THIS MSDS IS CURRENT AS OF February 6, 2008